# CANTILEVER ARM

Cantilever arms are used mainly for the fixing of pipes directly to walls. Other applications involve fixing and constructions on ceilings and floors. A wide range of structural desings can be created using the cantilever arms in connection with fixing rails and other components.

The cantilever arms include a removable end cap.

**Advantages:**

- Job-order manufacture of variable lengths.
- Massive and stable fixing.
- A wide range of sizes and lengths.
- Quality coating for long durability.

**Mounting procedure:**







| Technical data: | |
|---|---|
| Material: | zinc plated steel |
| Certificate: | No. 070-016998, AO 204 |

## Cantilever arm 27×18×1,25







| Code Supply number | Name | Shoe size (mm) | Spacing of shoe openings (mm) | Length (mm) | Type | Thickness T (mm) | Package (pc) | Weight (kg/100pcs) |
|---|---|---|---|---|---|---|---|---|
| 32271820 | Cantilever arm 27/18×200 (220) mm 1,25 zinc-pl. | 120×40 | 80 | 200 | 27/18 | 1,25 | 20 | 26,10 |
| 32271830 | Cantilever arm 27/18×300 (320) mm 1,25 zinc-pl. | 120×40 | 80 | 300 | 27/18 | 1,25 | 20 | 31,80 |
| 32271850 | Cantilever arm 27/18×500 mm 1,25 zinc-pl. | 120×40 | 80 | 500 | 27/18 | 1,25 | 10 | 42,60 |
| 32271860 | Cantilever arm 27/18×600 mm 1,25 zinc-pl. | 120×40 | 80 | 600 | 27/18 | 1,25 | 10 | 48,10 |

| Cantilever arms 27/18 (N) | Length L (mm) |
|---|---|
| 489 | 100 |
| 327 | 150 |
| 244 | 200 |
| 186 | 250 |
| 129 | 300 |
| 75 | 600 |

| Cantilever arms 27/18 (N) | Length L (mm) |
|---|---|
| 979 | 100 |
| 652 | 150 |
| 489 | 200 |
| 392 | 250 |
| 327 | 300 |
| 252 | 350 |
| 194 | 400 |
| 153 | 450 |
| 123 | 500 |
| 84 | 600 |

## Cantilever arm 28×30×1,75







| Code Supply number | Name | Shoe size (mm) | Spacing of shoe openings (mm) | Length (mm) | Type | Thickness T (mm) | Package (pc) | Weight (kg/100pcs) |
|---|---|---|---|---|---|---|---|---|
| 32283020 | Cantilever arm 28/30×200 (220) mm 1,75 zinc-pl. | 120×40 | 83 | 200 | 28/30 | 1,75 | 10 | 38,90 |
| 32283030 | Cantilever arm 28/30×300 (320) mm 1,75 zinc-pl. | 120×40 | 80 | 300 | 28/30 | 1,75 | 10 | 50,40 |
| 32283044 | Cantilever arm 28/30×440 mm 1,75 zinc-pl. | 120×40 | 80 | 440 | 28/30 | 1,75 | 10 | 67,20 |
| 32283050 | Cantilever arm 28/30×500 mm 1,75 zinc-pl. | 120×40 | 80 | 500 | 28/30 | 1,75 | 10 | 74,30 |
| 32283060 | Cantilever arm 28/30×600 mm 1,75 zinc-pl. | 120×40 | 80 | 600 | 28/30 | 1,75 | 1 | 85,10 |
| 32283075 | Cantilever arm 28/30×750 mm 1,75 zinc-pl. | 120×40 | 80 | 750 | 28/30 | 1,75 | 1 | 101,30 |
| 32283090 | Cantilever arm 28/30×900 mm 1,75 zinc-pl. | 120×40 | 80 | 900 | 28/30 | 1,75 | 1 | 120,60 |

| Cantilever arms 28/30 (30/30) (N) | Length L (mm) |
|---|---|
| 1731 | 100 |
| 1153 | 150 |
| 864 | 200 |
| 692 | 250 |
| 576 | 300 |
| 493 | 350 |
| 431 | 400 |
| 352 | 450 |
| 285 | 500 |
| 199 | 550 |
| 145 | 600 |
| 110 | 700 |
| 101 | 750 |
| 88 | 900 |

| Cantilever arms 28/30 (30/30) (N) | Length L (mm) |
|---|---|
| 3466 | 100 |
| 2310 | 150 |
| 1731 | 200 |
| 1385 | 250 |
| 1153 | 300 |
| 990 | 350 |
| 865 | 400 |
| 770 | 450 |
| 691 | 500 |
| 630 | 550 |
| 530 | 600 |
| 388 | 700 |
| 296 | 800 |
| 234 | 900 |