

GB Impact wrench
D Druckluft-Schlagschrauber
PL Klucz pneumatyczny
RUS Ударный пневматический гайковерт
CZ Klíč pneumatický
H Pneumatikus ütvecsavarozó
RO Pistol pneumatic
F Clé à choc pneumatique
I Chiave ad impulsi pneumatica
E Llave neumática de percusión
CN 气动扳手


COLOR
BOX



1/2"	TWIN HAMMER TYPE	0.63 MPa
12.5mm		
153 l/min	1150 Nm	10000 min ⁻¹
COMPOSITE BODY KOMPOZYTOWA OBUSOWA		
STANDARD		



TWIN HAMMER™
mechanism
ensuring resilience
to damage and
overload



$L_{wa} = 93.7 \pm 3.1$ dB;
 $L_{wb} = 104.7 \pm 3.1$ dB;
 $a_s = 4.4 \pm 0.4$ m/s²

YATO	Nm	
YT-09540	1150	10

GB Impact wrench
D Druckluft-Schlagschrauber
PL Klucz pneumatyczny
RUS Ударный пневматический гайковерт
CZ Klíč pneumatický
H Pneumatikus ütvecsavarozó
RO Pistol pneumatic
F Clé à choc pneumatique
I Chiave ad impulsi pneumatica
E Llave neumática de percusión
CN 气动扳手


COLOR
BOX



3/4"	TWIN HAMMER TYPE	0.63 MPa
19mm		
660 l/min	1300 Nm	5000 min ⁻¹
COMPOSITE BODY KOMPOZYTOWA OBUSOWA		
STANDARD		



TWIN HAMMER™
mechanism
ensuring resilience
to damage and
overload



$L_{wa} = 92 \pm 3$ dB;
 $L_{wb} = 103 \pm 3$ dB;
 $a_s = 5.47 \pm 1.5$ m/s²

YATO	Nm	
YT-09564	1300	4

GB Impact wrench
D Druckluft-Schlagschrauber
PL Klucz pneumatyczny
RUS Ударный пневматический гайковерт
CZ Klíč pneumatický
H Pneumatikus ütvecsavarozó
RO Pistol pneumatic
F Clé à choc pneumatique
I Chiave ad impulsi pneumatica
E Llave neumática de percusión
CN 气动扳手


COLOR
BOX



3/4"	TWIN HAMMER TYPE	0.63 MPa
19mm		
198 l/min	1630 Nm	5500 min ⁻¹
COMPOSITE BODY KOMPOZYTOWA OBUSOWA		
STANDARD		



TWIN HAMMER™
mechanism
ensuring resilience
to damage and
overload



$L_{wa} = 100.6 \pm 3.0$ dB;
 $L_{wb} = 111.6 \pm 3.0$ dB;
 $a_s = 10.21 \pm 1.5$ m/s²

YATO	Nm	
YT-09571	1630	6

GB Impact wrench
D Druckluft-Schlagschrauber
PL Klucz pneumatyczny
RUS Ударный пневматический гайковерт
CZ Klíč pneumatický
H Pneumatikus ütvecsavarozó
RO Pistol pneumatic
F Clé à choc pneumatique
I Chiave ad impulsi pneumatica
E Llave neumática de percusión
CN 气动扳手

BMC
& COLOR
SLEEVE



1"	PINLESS HAMMER TYPE	0.63 MPa
25mm		
560 l/min	2600 Nm	4000 min ⁻¹
COMPOSITE BODY KOMPOZYTOWA OBUSOWA		
STANDARD		



• application: automotive
service stations, trucks
• strong, uniform impact

• przeznaczenie: serwis,
samochody ciężarowe
• silny, jednolity uder

PINLESS HAMMER™
closed hammer
cage mechanism
prevents breakage
from hammer
pin damage



$L_{wa} = 94.1 \pm 2.8$ dB;
 $L_{wb} = 104.8 \pm 2.8$ dB;
 $a_s = 14.53 \pm 1.93$ m/s²

YATO	Nm	
YT-0959	2600	2